



Residential/Hospital/ Feature Light



Applications

- Recessed ceiling/wall light
- Indoor use only Jewelleystores
Museums
- No-dim

Description

- Unique slimline hi-brile design
- Provides feature/effect lighting
- Aluminum and polycarbonate
- Available in different lengths and wattages, colour temps and beam angle



Product Range

Code	DRS2W45*45WH	DRS4W75*45WH	DRS10W147*45WH	DRS20W280*45WH	DRS30W415*45WH
Watts	1*2W	2*2W	5*2W	10*2W	15*2W
Cutout	37*37mm	68*37mm	140*37mm	273*37mm	405*37mm
CRI	>80	>80	>80	>80	>91.6
Efficiency	80lm/W	80lm/W	90lm/W	80lm/W	60lm/W





Quick facts

Input power	15*2W
Power Factor	>0.963
IP Rating	20
Dimming	No
Luminous flux	1826.37lm
Color temperature	3000K
Color rendering index	>91.6
Beam Angle	30°
Fascia Colour	White
Installation	Recessed
Warranty	3 Years

Product Specifications

Supply Voltage	220-240VAC
Supply Frequency	50/60Hz
Cable	1.2M Flex&Plug
Body	Aluminium
Diffuser	PC+ABS
Driver	Fixed
Ambient Temp	-15°C to +45°C
Avg. lifetime	>50,000 hrs @ ta 25°C

Option

CCT	3000K/4000K/5000K
CRI	>70/ > 80/ > 90
COLOUR	White/Black/Silver
BEAM ANGLE	15°/30°/45°

