



Industrial/Commercial/ Retail/Cool rooms

Applications

- Outdoor washbays
- Mul-storey carparks
- Temporary lighting applications
- Commercial applications



Description

- Polycarbonate
- Easy mount configuration
- Emergency and sensor options
- Available in 24W and 80W version
- IK08 impact rating
- SS clips
- IP65 rated



Product Range

Code	TPMO48W1240*107WHE
Watts	48W
Dimension	1240mm*107mm
CRI	>80
Efficiency	105lm/W





Quick Facts

Watts	48W
Power Factor	>0.9
IP Rating	65
Dimming	No
Luminous Flux	5040lm
Color Temperature	4000K
Color Rendering Index(CRI)	>80
Beam Angle	120°
Fascia Colour	White
Installation	Surface Mounted
Function	Emergency(5W/3Hr)
Warranty	3 Years

Product Specifications

Supply Voltage	220-240VAC
Supply Frequency	50/60Hz
Cable	N/A
Body	PC
Diffuser	PC
Driver	Fixed
Ambient Temp	-20°C to +40°C
Avg. Lifetime	>30,000 hrs @ ta 25°C

Option

- CCT 3000K/4000K/5000K/6500K
- CRI >70/ > 80
- Function Emergency/Sensor

