



## Industrial/Commercial/ Retail/Cool rooms

### Applications

- Outdoor washbays
- Mul-storey carparks
- Temporary lighting applications
- Commercial applications



### Description

- Polycarbonate
- Easy mount configuration
- Emergency and sensor options
- IK08 impact rating
- SS clips
- IP65 rated



### Product Range

Code	TPMO80W1540*107WH	TPMO48W1240*107WH	TPMO24W640*107WH
Watts	80W	48W	24W
Dimension	1540mm*107mm	1240mm*107mm	640mm*107mm
CRI	>80	>80	>80
Efficiency	105lm/W	105lm/W	105lm/W





### Quick Facts

Watts	80W
Power Factor	>0.9
IP Rating	65
Dimming	No
Luminous Flux	8400lm
Color Temperature	4000K
Color Rendering Index(CRI)	>80
Beam Angle	120°
Fascia Colour	White
Installation	Surface Mounted
Warranty	3 Years

### Product Specifications

Supply Voltage	220-240VAC
Supply Frequency	50/60Hz
Cable	N/A
Body	PC
Diffuser	PC
Driver	Fixed
Ambient Temp	-20°C to +40°C
Avg. Lifetime	>30,000 hrs @ ta 25°C

### Option

- CCT 3000K/4000K/5000K/6500K
- CRI >70/ > 80
- Function Emergency/Sensor

